

borg&
overström

Under
Sink



An ultra-modern

The UnderSink epitomises leading design and innovation with its contoured tap and compact under-counter unit. This is our most discreet range and will fit into any environment seamlessly.



Power requirements
Hertz 50/Volts 220-240
Max power consumption
Chilled & Ambient 80W
Chilled, Ambient & Sparkling 100W

Chilled temperature
Min 2°C/Max 11°C
Throughput litres per hour
Chilled 22

Dimensions	WxDxH
Under counter	230x370x390mm
Tap height	405mm
Dispense height	250mm

Key Features

- Elegant, minimalistic design
- Discreet, hygienic control panel
- Compact under-counter unit
- Consistent low energy consumption
- Chilled, ambient and sparkling

Available accessories

- Sparkling Refill (CO₂ E290)
- CO₂ Regulator with Gauge
- Small Driptray
- Large Driptray
- Waste Kit with Level Sensor
- Sanitisation Kit
- Install Kit with Filter



Water options



Chilled



Ambient



Sparkling

Configuration



Undercounter

Recommended environment



Offices



Hospitality



Leisure

Number of users



1—5



6—10



11—25

u1 Models

Direct Chill, Complete Undercounter System, Chilled, Ambient—601151

Direct Chill, Complete Undercounter System, Chilled, Ambient, Sparkling—601152



Water system



Direct Chill

Borg & Overström Direct Chill utilises innovative technology to chill water instantly. We recommend this system for more demanding environments because of its optimum dispense performance and unrivalled hygienic qualities. Superior to the gravity fed Reservoir system, Direct Chill technology chills water on demand for the ultimate drinking experience.

Aqua Light Watercoolers
Berenkoog 91
1822 BN Alkmaar
T. 072-5761910
E. info@aqualight.nl
I. www.aqualight.nl

AQUA
light
Water | Coffee | and more